

ComTrack CATSE & CAT6

Maximum

SYSTEM FEATURES



- Provides surge protection against harmful transient voltages that are induced onto data lines and damage network.
- Compact footprint and universal mounting bracket allows installation flexibility.
- Use POE option for power over the Ethernet applications.
- · Can be used on 1Gb systems

PRODUCT SPECIFICATIONS

GENERAL SPECIFICATIONS

Applications: Data systems Design: Solid State fail-safe design

Warranty: 3-Year Unlimited Free Replacement

ELECTRICAL SPECIFICATIONS

Strength:

TK-CT2-CAT5E: 6000 Watts per unit TK-CT2-CAT5E-POE: 6000 Watts per unit TK-CT2-CAT6: 6000 Watts per unit TK-CT2-CAT6-POE: 6000 Watts per unit

Wires Protected: All wires. Response Time: < 1 nanosecond

Number of Protected Pairs (Wires): 4 Pair (8 wire)

MECHANICAL SPECIFICATIONS

Dimensions DIN2 Case: 3.94"L x 1.40"W x 2.28"H Dimensions CAT6 dongle/cord: 1.30"L x 1.30"W x 0.75"H

Enclosure Type: High-impact, non-metallic UL 94-5V

flame resistant rated

Connection Method: DIN2 Case: RJ45 In/Out (RJ45 female connections on both sides), Dongle: female

input with corded male output

Mounting Method: DIN2 units come standard with a case that allows the units to be screw or Din-Rail mounted. CAT6 dongle units hang in line with the CAT6 cable.

Operating Temperature: -40° C to 85° C (-40° F to



SPECIFICATIONS

Model Number	Description	Maximum Operating Voltage	Maximum Data Rate
TK-CT2-CAT5E-DIN2	4 Pairs (8 Wires) RJ45 IN/Out Standard CAT5e	7.5V	100 Mbps
TK-CT2-CAT5E-POE-DIN2	4 Pairs (8 Wires) RJ45 IN/Out Power Over Ethernet	56V	100 Mbps
TK-CT2-CAT6	4 Pairs (8 Wires) RJ45 IN/Out Standard CAT6	7.5V	1 Gbps
TK-CT2-CAT6-POE	4 Pairs (8 Wires) RJ45 IN/Out Power Over Ethernet	56V	1 Gbps
TK-CT2-CAT6-DIN2	4 Pairs (8 Wires) RJ45 IN/Out Standard CAT6	7.5V	1 Gbps
TK-CT2-CAT6-POE-DIN2	4 Pairs (8 Wires) RJ45 IN/Out Power Over Ethernet	56V	1 Gbps

DESCRIPTION

The Total Protections Solutions management team has pioneered the development of power conditioning and protection products for high end electronics for over 30 years. Total Protection Solutions is your one stop shop for all your residential and commercial surge suppression and power filtering needs. The TPS CAT5E & CAT6 offers the highest quality data line protection available. Strategically protect data pathways that are connected to network. Installing the CAT5E & CAT6 will reduce damage caused by surges that enter on these pathways and destroy routers, hubs and network devices.

Enclosure Dimensions with Dongle

CAT6: 1.30"L x 1.30"W x 0.75"H



TEL: 800-647-1911 www.tpssurge.com